
FIRE PROTECTION CABINET SERIES >BSS



- Active cooling system
- 2 Cable inlet / cable outlet
- 3 Fire protection housing
- 4 Swing lever door handle
- 6 Air inlet


1 RU = 44,45 mm (13/4").

H = overall height in mm

D = overall depth in mm W= overall width in mm h = useable height (inside) in mm d = useable depth (inside) in mm

w = useable depth (inside) in mm

| Models | Н | W | D | h | w | d | Weight |
|------------|------|------|-----|------|-----|-----|--------|
| BSS-3024 C | 1570 | 1050 | 775 | 1300 | 900 | 700 | 390 kg |
| BSS-3030 C | 1870 | 1050 | 775 | 1600 | 900 | 700 | 440 kg |
| BSS-3040 C | 2270 | 1050 | 775 | 2000 | 900 | 700 | 515 kg |



Description

BSS series fire protection cabinets are used in all places where voice evacuation systems have to accomplish the demands of E30 (functional endurance over 30 minutes in a case of fire) or F30 (resistance against fire for 30 minutes). BSS series housings are approved by the German construction supervision agency and fulfill all recent safety regulations (approval number Z-86.1-35).

The housings were tested in conjunction with our 19" swing frame cabinets of the RSS series by MPA Stuttgart. The comprehensive test report can be requested if needed.

The design of BSS series is tuned to fit perfectly around the swivel door racks of our RSS series (RSS-5524B, RSS-5530 B, RSS-5540 B). Due to their spacious dimensions they can of course be used with a variety of other 19" racks as

Please consider the following features:

- Fire resistant housing with the capacity to withstand a fire on its outside for 30 minutes
- Complies with the demands of the recent MLAR (German regulation for high buildings)
- Fire resistant plates according to DIN 4102 A1/A2
- 60 minutes fire load dampening (I60)
- Protection class II (IP 54)
- Integrated, powered cooling system(double \varnothing 80 mm fans)
- Two cable inputs in the top of the housing
- Double door with covered steel hinges
- Upgrade with a special locking cylinder is possible
- Wall mounting kit included
- Colour RAL 7035 (light grey)



FIRE PROTECTION CABINET SERIES >BSS



