

Accessories

Charger-Kit

for 2 pcs. UBH-016



Charger for 2 handheld microphones UBT-016. Power supply included.

Charger-Kit ACS-002

for 2 pcs. UBH-016

Charger-Kit

for 8 pcs. UBR-016 or UBT-016



Charger Kit for up to 8 receivers or transmitters. Power supply included.

Charger-Kit ACS-008

for 8 pcs. UBR-016 or UBT-016

Charger-Bag

for 20 pcs. UBR-016 or UBT-016



Convenient carrying case with integrated charger for up to 20 receivers or transmitters.

Charger-Bag ACS-020

for 20 pcs. UBR-016 or UBT-016

Charger-Case

for 40 pcs. UBR-016 or UBT-016



Stable Charging Case for up to 40 receivers or transmitters. Additional space for headphones and microphone power supply. With extendable handles and wheel for an easy transport.

Charger-Case . ACS-040

for 40 pcs. UBR-016 or UBT-016

19"-Rack Mounting-Set

for 1 pcs. UWT-016



19" Mounting bracket for the fixed transmitter UWT-016. With TNC connector for front mounting of the antenna.

Mounting-Set . RU-501 T

1 RU, for 1 pcs. UWT-016

Battery Set AAA

rechargeable, for UBR-016 / UBT-016



Set contents 2 pieces NiMH batteries (AAA).

Battery Set UBA-002

2x NiMH AAA; for UBR-016 / UBT-016

Battery Set AA

rechargeable, for UBH-016



Set contents 2 pieces NiMH batteries (AA).

Battery Set UBB-002

2x NiMH AA; for UBH-016

Technical data	UBR-016 RECEIVER
Frequency range	863 – 865 MHz (16 frequencies)
Transmission type	PLL synth.
Signal to noise ratio	80 dB
Audio-frequency range	50 Hz – 15 kHz ± 3 dB
Audio output line	0dB
Headphone output	3,5 mm jack
Max hub	± 40 kHz
Power supply	2x Micro (1,5V; AAA) or rechargeable battery
Range	50 – 80 m
Dimensions / weight	W 60 mm x H 85 mm x D 19 mm; approx. 60 g

Technical data	UBT-016 TRANSMITTER
Frequency range	863 – 865 MHz (16 frequencies)
Transmission type	PLL synth.
Signal to noise ratio	80 dB
Audio-frequency range	50 Hz – 15 kHz ± 3 dB
Audio output line	0dB
Microphone input	3,5 mm, jack
Max. Hub	± 40 kHz
Power supply	2x Micro (1,5V; AAA) or rechargeable battery
Range	50 – 80 m
Dimensions / weight	W 60 mm x H 85 mm x D 19 mm; approx. 60 g

Technical data	UWT-016 TRANSMITTER
Frequency range	863 – 865 MHz (16 frequencies)
Modulation	FM
Transmission type	PLL synth.
RF Output Power	10 mW
Audio-frequency range	50 Hz – 15 kHz ± 3 dB
Max. Hub	± 48 kHz
Power supply	DC 12V
Range	50 – 80 m
Dimensions / weight	W 210 mm x H 44 mm x D 190 mm; 150 g

Technical data	UBH-016 TRANSMITTER
Frequency range	863 – 865 MHz (16 frequencies)
Modulation	FM
Transmission type	PLL synth.
RF Output Power	10 mW
Audio-frequency range	50 Hz – 15 kHz ± 3 dB
Max. Hub	± 40 kHz
Power supply	2x Mignon (1,5V; AA) or rechargeable battery
Range	50 – 80 m
Dimensions / weight	W 37 mm x H 165 mm x D 28 mm; 100 g