

100V


60W Adaptors
7,5/15/30/60W

2-Way-System



Certificat No.
1488-CPR-0315/W

Under fire
regulation



Description

This loudspeaker is tested by a notified product certification authority and certified to EN 54-24:2008.

This music horn speaker series fulfilled the requirements of EN 54-24 and British standard BS 5839.

The new music horn CS-6HT60WHBS combines sound pressure and weatherproof of horn speaker with excellent sound of 2-way-system. It is particularly suitable for applications, where apart from speech also a high quality music performance is required.

The weatherproof construction (protection type IP-66) allows the permanent use outdoors. Therefore the range of application possibilities is greatly extended.


Please consider the following features:

- The housing is made of impact proof ABS-plastic and can be painted in all RAL colors on option.
- 100V-transformers are used, enabling various tapping's

- Equipped with a ceramic terminal and a metallic cable cover complies with the requirements of BS speakers de 5839.
- The music horn contains two separate driver units, one for the low and one for the high frequency range.
- The mounting bracket is tilt able so the music horn speaker is optimally suited for wall- or ceiling mounting.



| Technical data | CS-6HT60 BS |
|------------------------------|---|
| Load rating (Music Power) | 60 W (90 W) |
| Base impedance | 8 ohms |
| Adaptors at 100V | 60 - 30 / 15 / 7,5 W |
| Frequency range (±10dB) | 100 - 20.000 Hz |
| Sound pressure 1 W/1 m | 97 dB |
| Sound pressure SPL Pmax/1 m | 115 dB |
| Angle of refl. beam (1 kHz) | 60° |
| Protection Type DIN 40050 | IP 66 |
| Dimensions (without bracket) | 330 x 430 x 415 mm |
| Material, Colour | ABS-plastic UL94V0, light gray (RAL-7035) |
| Weight | 7,05 kg |



Model designation

Alarming Music Horn, 60W..... CS-6HT60 BS
20 W, with 100V-transformer, light gray