

BALL SPEAKERS

100 V

PASSIVE

ACTIV








Description

The ball speakers KL-520 are made of high-quality impact and scratch resistant plastic and are splash water proof. Its surface can be painted in all colours.

The ball speakers are very efficient where low hanging speakers are required, for example rooms with high ceilings.

Please consider the following features:

 Perfect playback quality is ensured by a wide banded and powerful speaker case.



Technical data	KL-520
Load rating (Music power)	20 W (30 W)
Transformer tappings at 100 V	20 / 10 / 5 W
Frequency range	140 – 14.500 Hz
Sound pressure at 1W/1m	95,5 dB
Sound pressure SPL Pmax/1m	109 dB @1,5kHz
Angle of refl. beam (-6dB) 1/4/8 kHz	180°/ 50°/ 30°
Speaker Ø (mm) and Impedance	125 mm / 8 ohms
Dimensions Ø x H (mm)	184,5 x 162,5 mm
Weight, Colour	approx. 1,8 kg, white

- The high-quality matching transformer is designed for 100 V and 70 V. It can also be connected to 1/1 − 1/2 − 1/4 performance and low-impedance (8 ohms), the cable conductors are marked.
- The installation is theft save. The speaker suspension can be adjusted up to 5m.

at 100V:

1/1 (orange)
1/2 (gray)
1/4 (white)
com (black)

Supplied with: connection cable 5 m, ceiling canopy.

Model designation

Ball Speaker, 20 W KL-520 white, with 100V-transformer