



600W
2 SPEAKER SYSTEM
+300W (optional)

UHF-SYSTEM:
Registration and
Free of charge!

- Compact PA-System
- Mobile usage for up to 400 listeners
- Wireless UHF technology (expandable to 4-channel)

This mobile PA-System PCS-500 has **3x 300W (RMS)** performance and is suited for professional sounding for up to 400 people. Optimal results can be achieved through carefully selected, complementary components. This compact and user friendly system can be ready for operation within a few minutes. The mobile set of wheels makes handling very easy with little effort.

This system includes the following components:

- 1x PMX-911 R Power Mixer 3x 300W (RMS)**
Including 9 input-channels (4x stereo-CH) and diversity of outputs
- 2x QRF-210 Professional 2-Way Speaker**
Full Range, including 10m Connection cables each
- 2x Floor Stands**
Adjustable height from 115 cm up to 200 cm
- 1x CD / MP3 / DVD-Player with Remote**
The unit will play all common audio formats such as: CD/CD-R/RW, MP3, VCD, SVCD, DVD, DVD+R/RW, WMA, Picture CD and XviD
- 1x UHF Receiver-System, 1-Channel**
16 frequencies (registration free), with wireless Hand microphone optionally expandable up to 4 channels (see UR-016 B/C on page 238)
- 1x Professional Rack-Flightcase**
19", 10 RU, with rounded corners and 25mm aluminum edge protection

Please consider the following:

The PCS-500 System will be delivered fully assembled and is best suited for mobile usage as well as stationary operation. Please extract further technical data regarding the individual components from our main catalogue.

★

Technical data		PCS-500	
Mixer	Inputs	9x Mic In:	-50dBu
	Inputs CH1-7 (mono)	Line in:	-20dBu
	Inputs CH8-11 (stereo)	Line in:	-10dBu
		1x Aux In:	-10dBu
1x Tape In:		-10dBu	
RMS/Program power		3x 300/900W at 4 ohms; 3x 200/300W at 8 ohms	
Speaker		220W (RMS), 350W (MAX), with Speaker IN/Out; Fullrange with 1,29" tweeter, 10" bass-woofer	
Speaker Floor Stand		Aluminium tube Ø 36mm, adjustable 115-200mm,	
Microphone Wireless System		UHF 16 frequencies (863-865 MHz), 1-channel	
System	Power supply	220V – 240V/AC, 50–60 Hz	
	Power absorption	approx. 1.350W	
	Dimensions/Weight	W 550 x H 510 x D 500mm (Angle-Flightcase); 75 kg	

PORTABLE COMPACT-SYSTEM, 600/+300W ... PCS-500
with 2 professional 2-way speakers and accessories (see image)