



1200W
4 SPEAKER SYSTEM

UHF-SYSTEM:
Registration and
Free of charge!

- Compact PA-System
- Mobile usage for up to 1.200 listeners
- Wireless UHF technology (expandable to 4-channel)

This mobile PA-System PCS-1200 has **2x 600W** (RMS) performance and is suited for professional sounding for up to 1.200 people. Optimal results can be achieved through carefully selected, complementary components. This compact and user friendly system can be ready for operation within a few minutes. The mobile set of wheels makes handling very easy with little effort.

Please consider the following:

The PCS-1200 System will be delivered fully assembled and is best suited for mobile usage as well as stationary operation.

This system includes the following components:

- 1x PMX-1216 Power Mixer 2x 600W (RMS)**
Including 16 input-channels (8x Mono-CH) and diversity of outputs
- 4x QRF-212 Professional 2-Way Speakers**
Full Range, including 10m Connection cables each
- 4x Floor Stands**
Adjustable height from 115 cm up to 200 cm
- 1x CD/MP3/SD-Card/USB player**
with pitchable CD player and remote control
- 1x UHF Receiver-System, 1-Channel**
16 frequencies (registration free), with wireless Hand microphone optionally expandable up to 4 channels (see UR-016 B/C on page 238)
- 1x Professional Angle-Flightcase**
19", 10 RU, incl. rack rail lifting device on the top and mobile set of wheels
- Various Accessories**
Including Rack drawer, Connection Cable, Power splitter, etc.

ation. Please extract further technical data regarding the individual components from our main catalogue.

★

Technical data		PCS-1200
Mixer	Inputs CH1-8 (mono)	Mic In: -55dBu (1,38mV) 50-600 ohms,
	Inputs CH9-16 (stereo)	Line In: -35dBu (13,8mV), 600 ohms
		Stereo In: 0dBu (775mV), 600 ohms
	RMS/Program power	2x 600/900W at 4 ohms; 2x 350/520W at 8 ohms
Speaker	Sound Control Channel	Highs: 12kHz shelving ±15dB
		Mids: 2,5kHz peaking ±12dB
		Mids for CH 1-4: semiparam. 100Hz-8kHz ±12dB
		Lows: 80Hz shelving ±15dB
		Low Cut: 18dB/Okt. @ 75Hz
Speaker		250W (RMS), 400W (MAX), with Speaker IN/Out; 1,29" tweeter, 12" Fullrange
Floor Stand		Aluminium tube Ø 36mm, adjustable 115-200mm,
Microphone Wireless System		UHF 16 frequencies (863-865 MHz), 1-channel
System	Power supply	220V – 240V/AC, 50–60 Hz
	Power absorption	approx. 2.200W
	Wheels	4 steering rollers 100 mm, 2 with brakes (Blue-Wheels)
	Dimensions/Weight	W 550 x H 570 x D 560mm (Angle-Flightcase); 43 kg

PORTABLE COMPACT-SYSTEM, 1200W PCS-1200
with 4 professional 2-way speakers and accessories (see image)