PORTABLE COMPACT-SYSTEME



RES









- Cabaret and small theaters
- trade fairs and exhibitions
- party tents and celebrations
- sports events
- advertising and sports events



PORTABLE COMPACT-SYSTEM PCS-500

COMPACT PA-SYSTEM FOR MORILE OPERATION



This mobile PA-System PCS-500 has **3x 300W** (RMS) performance and is suited for professional sounding for up to 400 people. Optimal results can be achieved through carefully selected, complementary components. This compact and user friendly system can be ready for operation within a few minutes. The mobile set of wheels makes handling very easy with little effort.

This system includes the following components:

- 1x PMX-911R Power Mixer 3x 300W (RMS) Including 9 input-channels (4x stereo-CH) and diversity of outputs
- 2x QRF-210 Professional 2-Way Speaker Full Range, including 10m Connection cables each
- 2x Floor Stands

Adjustable height from 115 cm up to 200 cm

- 1x CD / MP3 / DVD-Player with Remote
 The unit will play all common audio formats such as: CD/CD-R/RW, MP3, VCD, SVCD, DVD, DVD+R/RW, WMA, Picture CD and XviD
- 1x UHF Receiver-System, 1-Channel
 16 frequencies (registration free), with wireless Hand microphone
 optionally expandable up to 4 channels (see UR-016B/C on page 238)
- 1x Professional Rack-Flightcase
 19°, 10 RU, with rounded corners and 25mm aluminum edge protection

Please consider the following:

The PCS-500 System will be delivered fully assembled and is best suited for mobile usage as well as stationary operation. Please extract further technical data regarding the individual components from our main catalogue.

Technical data		PCS-500		
Mixer	Inputs	9x Mic In:	-50dBu	
	Inputs CH1-7 (mono)	Line in:	-20dBu	
	Inputs CH8-11 (stereo)	Line in: 1x Aux In: 1x Tape In:	-10dBu -10dBu -10dBu	
RMS/Program power		3x 300/900W at 4 ohms; 3x 200/300W at 8 ohms		
Speaker		220W (RMS), 350W (MAX), with Speaker IN/Out; Fullrange with 1,29" tweeter, 10" bass-woofer		
Speaker Floor Stand		Aluminium tube Ø 36mm, adjustable 115-200mm,		
Microphone Wireless System		UHF 16 frequencies (863-865 MHz), 1-channel		
System	n Power supply 220V – 240V/AC, 50~60 Hz		//AC, 50~60 Hz	
	Power absorption	approx. 1.350W		
	Dimensions/Weight	W 550 x H 510 x D 500mm (Angle-Flightcase); 75 kg		

PORTABLE COMPACT-SYSTEM, 600/+300W...PCS-500

with 2 professional 2-way speakers and accessories (see image)

PCS-600 PORTABLE COMPACT-SYSTEM

COMPACT PA-SYSTEM FOR MOBILE OPERATION





This mobile PA-System PCS-600 has 2x 300W (RMS) performance and is suited for professional sounding for up to 600 people. Optimal results can be achieved through carefully selected, complementary components. This compact and user friendly system can be ready for operation within a few minutes. The mobile set of wheels makes handling very easy with little effort.

Please consider the following:

The PCS-600 System will be delivered fully assembled and is best suited for mobile usage as well as stationary oper-

This system includes the following components:

- 1x PMX-614 Power Mixer 2x 300W (RMS) Including 14 input-channels (6x Mono-CH) and diversity of outputs
- 2x QRF-212 Professional 2-Way Speakers Full Range, including 10m Connection cables each
- 2x Floor Stands

Adjustable height from 115 cm up to 200 cm

- 1x CD/MP3/SD-Card/USB player with pitchable CD player and remote contro
- 1x UHF Receiver-System, 1-Channel 16 frequencies (registration free), with wireless Hand microphone optionally expandable up to 4 channels (see UR-016 B/C on page 238)
- 1x Professional Angle-Flightcase 19", 10 RU, incl. rack rail lifting device e on the top and mobile set of wheels
- Various Accessories

Including Rack drawer, Connection Cable, Power splitter, etc.

ation. Please extract further technical data regarding the

individual components from our main catalogue.

Technical data		PCS-600		
Mixer	Inputs CH1-6 (mono)	Mic In:	-55dBu (1,38mV) 50-600 ohms,	
	Inputs CH7-14 (stereo)	Line in: Stereo In:	-35dBu (13,8mV), 600 ohms 0dBu (775mV), 600 ohms	
	RMS/Program power	2x 300/450W at 4 ohms; 2x 200/340W at 8 ohms		
	Sound Control Channel	Highs: Mids: Mids for CH Lows: Low Cut:	12kHz shelving ±15dB 2,5kHz peaking ±12dB 1-3: semiparam. 100Hz-8kHz ±12dB 80Hz shelving ±15dB 18dB/Okt.@ 75Hz	
Speaker		250W (RMS), 400W (MAX), with Speaker IN/Out; 1,29" tweeter, 12" Fullrange		
Floor Stand		Aluminium tube Ø 36mm, adjustable 115-200mm,		
Microphone Wireless System		UHF 16 frequencies (863-865 MHz), 1-channel		
System	Power supply	220V - 240V/AC, 50~60 Hz		
	Power absorption	approx. 1.200W		
	Wheels	4 steering rollers 100 mm, 2 with brakes (Blue-Wheels)		
	Dimensions/Weight	W 550 x H 570 x D 560mm (Angle-Flightcase); 43 kg		

PORTABLE COMPACT-SYSTEM, 600WPCS-600

with 2 professional 2-way speakers and accessories (see image)



PORTABLE COMPACT-SYSTEM PCS-1200

COMPACT PA-SYSTEM FOR MORILE OPERATION



This mobile PA-System PCS-1200 has **2x 600W** (RMS) performance and is suited for professional sounding for up to 1.200 people. Optimal results can be achieved through carefully selected, complementary components. This compact and user friendly system can be ready for operation within a few minutes. The mobile set of wheels makes handling very easy with little effort.

Please consider the following:

The PCS-1200 System will be delivered fully assembled and is best suited for mobile usage as well as stationary oper-

This system includes the following components:

1x PMX-1216 Power Mixer 2x 600W (RMS)
Including 16 input-channels (8x Mono-CH) and diversity of outputs

4x QRF-212 Professional 2-Way Speakers
Full Range, including 10m Connection cables each

4x Floor Stands
Adjustable height from 115 cm up to 200 cm

1x CD/MP3/SD-Card/USB player
with pitchable CD player and remote control

1x UHF Receiver-System, 1-Channel
16 frequencies (registration free), with wireless Hand microphone
optionally expandable up to 4 channels (see UR-016B/C on page 238)

1x Professional Angle-Flightcase
19°, 10 RU, incl. rack rail lifting device on the top and mobile set of wheels
Various Accessories

Including Rack drawer, Connection Cable, Power splitter, etc.

ation. Please extract further technical data regarding the individual components from our main catalogue.

*

Technical data		PCS-1200		
Mixer	Inputs CH1-8 (mono)	Mic In:	-55dBu (1,38mV) 50-600 ohms,	
	Inputs CH9-16 (stereo)	Line in: Stereo In:	-35dBu (13,8mV), 600 ohms 0dBu (775mV), 600 ohms	
	RMS/Program power	2x 600/900W at 4 ohms; 2x 350/520W at 8 ohms		
	Sound Control Channel	Highs: Mids: Mids for CH Lows: Low Cut:	12kHz shelving ±15dB 2,5kHz peaking ±12dB 1-4: semiparam. 100Hz-8kHz ±12dB 80Hz shelving ±15dB 18dB/Okt. @ 75Hz	
Speaker		250W (RMS), 400W (MAX), with Speaker IN/Out; 1,29" tweeter, 12" Fullrange		
Floor Stand		Aluminium tube Ø 36mm, adjustable 115-200mm,		
Microphone Wireless System		UHF 16 frequencies (863-865 MHz), 1-channel		
System	Power supply	220V – 240V/AC, 50~60 Hz		
	Power absorption	approx. 2.200W		
	Wheels	4 steering rollers 100 mm, 2 with brakes (Blue-Wheels)		
	Dimensions/Weight	W 550 x H 570 x D 560mm (Angle-Flightcase); 43 kg		

PORTABLE COMPACT-SYSTEM, 1200W..... PCS-1200

with 4 professional 2-way speakers and accessories (see image)