

20W Adaptions
5/10/20W

Xorva S
S E R I E

40W Adaptions
10/20/40W



100V

PASSIVE

ACTIVE

Description


The **XORVA S** series is designed for indoor use. It offers two alternative models (passive or 100V) in two performance classes each.

This speaker series is characterized by the handy and inconspicuous design.

The compact housing speakers can be attached in any corner thanks to their oval characteristics.

In addition, the pivoting, tilting and rotating mounting bracket allows easy alignment of the speaker on the wall.

The new compact loudspeaker series meets all requirements for restaurants, presentations, classrooms, and much more.



Please consider the following features:

- Available in 2 different versions (passive or 100V).
- The high-quality, shapely oval plastic housing ensures perfect boom and swing freedom.
- Supplied with swiveling and tiltable metal wall bracket.
- Designed for indoor installation in restaurants, presentation rooms, schools, and more.
- The powerful 4" broadband chassis provides a nice and quiet sound with good speech audibility.

★

Technical data	XSS-020	XSS-020 T
Type	PASSIVE	100V
Nominal load capacity (program)	20 (40) W	20 (40) W
Adjustments at 100V	-	20 - 10 - 5 W
Inputs	Clamp L/R	
Impedance	6 ohms	6 ohms
Frequency range (±10dB)	132 - 20.000 Hz	
Sound pressure at 1W/1m	85 dB (±3dB)	
Sound pressure SPL Pmax/1m	100 dB (±3dB)	
Beam angle (-6dB) 1/2/4 kHz	110°/65°/55°	
Speaker Ø	77 mm, Tweeter 20,4 mm	
External dimensions (HxWxD)	175x115x107 mm	
Colour / Weight	white; 800 g	white; 1,2kg

Model designation

Xorva S Speaker, 20W **XSS-020**
passive speaker, 6 ohms, with mounting bracket

Xorva S Speaker, 20W **XSS-020 T**
with 100V-transformer, with mounting bracket

Technical data	XSS-040 T
Type	100V
Nominal load capacity (program)	40 (50) W
Adjustments at 100V	40 - 20 - 10 W
Inputs	Clamp L/R
Impedance	6 ohms
Frequency range (±10dB)	76 - 18.000 Hz
Sound pressure at 1W/1m	90 dB (±3dB)
Sound pressure SPL Pmax/1m	108 dB (±3dB)
Beam angle (-6dB) 1/2/4 kHz	115°/55°/35°
Speaker Ø	106 mm, Tweeter 25,4 mm
External dimensions (HxWxD)	206x140x136 mm
Colour / Weight	white; 2,3 kg

Model designation

Xorva S Speaker, 40W **XSS-040 T**
with 100V-transformer, with mounting bracket